

☀ Specification

PRODUCT SPECIFICATION

CPU	Pentium® M 2.0 GHz		
Chipset	Intel® E7501 + ICH3 + P64H2		
Memory	DDR 1GB (512MB * 2)		
Storage	128MB DOM		
Ethernet	Four GbE controllers (two with copper and two with SFP ports) Three 10/100Mbps Ethernet ports		
I/O Port	One USB 2.0 port and one DB-9 console port		
Power Supply	200W ATX power supply		
Environment		Temperature	Humidity
	Operating	32 to 104°F (0 to 40°C)	5 to 95% relative humidity, non-operating, non-condensing
	Storage	-4 to 167°F (-20 to 75°C)	
Dimension (W x D x H)	440mm(W) x 325mm(D) x 44mm(H) (17.3"W x 12.8"D x 1.7"H)		

NETWORK MANAGEMENT

Remote Management	HTTPs, Telnet, SSH, SNMP (v1, v2c, 3), SNMP Proxy, Back up and Restore configuration files
MIB	MIB II for IP (RFC 1213), Ethernet MIB, GSI Private MIB, 802.11 MIB
NTP Synchronization	RFC 1305
Syslog	Remote Activity Syslog
Reset	Remote reset
Firmware Upgradeable	Remote Firmware upgrade via HTTPs
Back up and Restore	Remotely Back up and Restore configuration files

REGULATORY

Certification	FCC, CE
Compliance	RoHS

WARRANTY

One Year

RELATED PRODUCT

Access Point	BW1230 SMB Wireless Router BW1250 Dual Radio 2.4GHz/5GHz Access Point BW1330 High Performance Hotspot Access Point BW2250 Dual Radio 2.4GHz/5GHz Outdoor Access Point
--------------	--