



# MerryIoT Sensors & App

## Quick Installation Guide

# Content

1. Safety Warning.....	3
2. Open Box Content List.....	4
3. Sensor Input/ Output.....	6
4. Sensor Introduction.....	8
5. Sensor Installation.....	9
6. Sensor APP functions.....	17
7. Battery Replacement.....	21
8. FAQ.....	26
9. Copyright Notice.....	27



# Safety Warning

### Read this manual before attempting to install the device!

Failure to observe recommendations included in this manual may be dangerous or cause a violation of the law. The manufacturer, **Browan Communications Inc.** will not be held responsible for any loss or damage resulting from not following the instructions of this user manual.

- The device must not be dismantled or modified in any way.
- The device is only intended for indoor use. Do not expose it to moisture.
- The device is not intended to be used as a reference sensor, and **Browan Communications Inc.** will not be held liable for any damage which may result from inaccurate readings.
- The battery should be removed from the device if it is not to be used for an extended period. Otherwise, the battery might leak and damage the equipment. Never leave a discharged battery in the battery compartment.
- The device must never be subjected to shocks or impacts.
- To clean the device, wipe with a soft moistened cloth. Use another soft, dry cloth to wipe dry. Do not use any detergent or alcohol to clean the device.

## Contact Us

Website: <https://www.merryiot.com>


E-mail: [sales@merryiot.com](mailto:sales@merryiot.com)  
[support@merryiot.com](mailto:support@merryiot.com)

Address : Browan Communications Incorporation  
No.15-1 Zhonghua Rd., Hsinchu Industrial Park,  
Hukou, Hsinchu, Taiwan, 30352


Copyright © 2022 Browan Communications Inc.

# Chapter 2 - Package Content

## MerryloT Air Quality CO2(CD10)




## MerryloT Motion Detection(MS10)






## Chapter 2 - Package Content


### MerryIoT Open / Close(DW10)




### MerryIoT Leak Detection(WL10)




### MerryloT Air Quality CO2(CD10)




### MerryloT Motion Detection(MS10)



MerryIoT Open / Close(DW10)



MerryIoT Leak Detection(WL10)



## Chapter 4 - Sensor Introduction



MerryIoT Air Quality CO2  
CD10

MerryIoT Air Quality CO2 sensor (CD10) is a professional LoRaWAN smart device. Its minimalistic design makes it ideal for mounting on walls at home or at work. It provides full surveillance over the CO2 levels, temperature, and humidity.

### Features:

- 3 sensors in 1 (CO2 & Temperature & Humidity)
- Built-in buzzer for alarm if the CO2 level is more than 1000 ppm
- Years of battery lifetime
- LoRaWAN technology with a long communication distance
- Coverage test button for easy installation



MerryIoT Motion Detection  
MS10

MerryIoT motion detector (MS10) is an easy step to a safer home. Monitor front and back doors, driveways, sheds, garages, and gates. It can be applied to all your properties. It provides an additional level of security and safety to your properties and protects your loved ones. Not to mention is alerts you in case of emergency.

### Features:

- 4 sensors in 1 (PIR & Temperature & Humidity & Vibration)
- Detect human presence accurately
- LoRaWAN technology with a long communication distance
- Coverage test button for easy installation
- Alarm message for the device is been moved or tampered
- Years of battery lifetime
- Ultrawide range detection
  - 125° Horizontal
  - 100° Vertical
  - Up to 7 m distance



MerryIoT Open / Close  
DW10

The MerryIoT Open/Close sensor (DW10) give you a peace of mind, anywhere, anytime. Get real time alerts at the exact moment you have unexpected guests, broken windows, opened safes, an opened mailbox or escaped pets.

### Features:

- 4 sensors in 1 ( Open/Close & Temperature & Humidity & Vibration)
- Years of battery lifetime
- LoRaWAN technology with a long communication distance
- Alarm message for the device is been moved or tampered
- Coverage test button for easy installation

## Chapter 4 - Sensor Introduction



MerryloT Leak Detection  
WL10


The MerryloT Water Leak Sensor (WL10) will in real-time alert you the moment it comes in contact with leaking water. Don't ever worry about leaks or floods in your basement, under your sinks, from your water heater, or anywhere else in the house.

### Features:

- 4 sensors in 1 (Drip/Leak/Flood & Temperature & Humidity & Vibration)
- Built-in water-sensing probes on top and bottom for leak/flooding detection
- Years of battery lifetime
- LoRaWAN technology with a long communication distance
- Coverage test button for easy installation
- Alarm message for the device is been moved or tampered

## Chapter 5 - Sensor Installation

- 1 Please make sure you have Helium coverage before installing the MerryloT Sensors.
  1. Best senerio is you already have a Helium miner up and running.
  2. If you don't have a Helium miner running, you need to check your neighborhood's helium coverage. Go to <https://explorer.helium.com> and follow the following steps.
- 1 Press "find my location" icon, and the map will redirect to the vicinity of your location.
- 2 According to the vicinity of your location, to find your accurate location to see if any Helium coverage around here.




\*Annotation: Hexagons in Helium, it is a semi-precise point location covering 300 m<sup>2</sup> (3200 ft<sup>2</sup>), which is comparable to the footprint of a large house. The number display on the Hexagons, it means how many Helium hotspot is been asserted location here, you could imagine that how many Helium hotspots installed in 300 m<sup>2</sup> (3200 ft<sup>2</sup>).

## Chapter 5 - Sensor Installation

- 2 Install and launch MerryIoT mobile application on your phone



\*Search:MerryIoT Sensor




- 3 Register your account.

### Sign in by social media


- 1 Press Sign In




- 2 select Sign In WITH GOOGLE/FACEBOOK/APPLE



- 3 Add your group, you will see the main view after



Sign In successfully




### Create an account


- 1 Press Sign Up




- 2 Fill in your information




- 3 Confirm your mail (fill in the verification code)



- 4 Press Sign In and select "Sign In WITH EMAIL"





- 5 Add your group, you will see the main view after




# Chapter 5 - Sensor Installation

## 4 Add your device to the App

MerryIoT Air Quality CO<sub>2</sub>  
CD10



After scan





fill in the name and the location




Click the "complete", after the group page show, you successfully added your sensors!


MerryIoT Motion Detection  
MS10



After scan





fill in the name and the location




Click the "complete", after the group page show, you successfully added your sensors!

## Chapter 5 - Sensor Installation


### MerryIoT Open/Close DW10



After scan





fill in the name and the location




Click the "complete", after the group page show, you successfully added your sensors!


### MerryIoT Leak Detection WL10



After scan



fill in the name and the location



Click the "complete", after the group page show, you successfully added your sensors!




## Chapter 5 - Sensor Installation

- 5 When the sensor is successfully online, the LED will go on to constant lumination for 3 seconds.
- 6 Once the Sensor is successfully connected, the following icon will appear on the dashboard  
\*Press the button on the sensor, the sensor's real-time status will be updated.

MerryIoT Air Quality CO2  
CD10




MerryIoT Motion Detection  
MS10



MerryIoT Open/Close  
DW10



MerryIoT Leak Detection  
WL10



## Chapter 5 - Sensor Installation


- 7 Once the Sensor is connected, install the Sensor to your desired location

### MerryloT Air Quality CO2(CD10)

It is important to know, that the CO2 sensor unit should be mounted at 48 inches or 122cm above the floor, and they should not be near outside doors or windows that can make the space appear to have more fresh air than it actually does. Think of CO2 flowing like water. Water will fill a cup from the bottom upwards. The same will happen in interior spaces like draft coolers, restaurants, breweries, and grow facilities. Because the CO2 gas is heavier than normal air it will flow down stairs or collect in low lying areas first.

So, please avoid these placement:

- Restricted air flow
- In direct sunlight from windows
- Close to heat source



### MerryloT Motion Detection(MS10)

Assets where intruders are most likely to enter, or other applications like occupied space purpose.

Places like:

1. Garage Entrance (for security purpose)


The eye of the sensor should point to the direction where the intruders may come from.

2. Meeting Room (for occupied space purpose)

It is recommended to install 2 MerryloT Motion Detections in one space where you would like to know whether the space is occupied or not.

One with the eye of the sensor pointing the entrance of the space, and the other one pointing at where people assumed to be stayed in the space, the meeting table in this case.

Meeting Room




Garage Entrance



### MerryloT Open/Close(DW10)

1. Clean the installaon area.
2. Remove the protecve layer from the double-sided tape on the door sensor, place the door sensor in the desired-posion(the fixed part of your door or window), and press firmly for at least 5 seconds.
3. Remove the protective layer from the double-sided tape on the magnet, place the magnet in the desired postion(algn the magnet marking with the hall sensor marking on the sensor), and press firmly for at least 5 seconds.

\*Note: the maximum sensing distance is 10mm.




In any rooms / mailbox  
on the window or door

### MerryloT Leak Detection(WL10)

The most common application for our water detection sensors is underneath AC units that are susceptible to leaks. However, it is important to ensure you cover other potential threats such as existing pipework, heating systems, kitchens, toilets and areas that may be likely to flood first in the event of extreme weather conditions (by doors/windows)

It is recommended to install mulitple MerryloT Leak Detection in one space, where the potential leakage may occure.


1. For Home basement use
2. For server rooms and data centers




In the kitchen cabinet,  
where the water pipes locate

## Chapter 6 - APP Functions

### MerryIoT Air Quality CO2(CD10)




### Icons



Both the icon of Temperature and Relative Humidity will be updated by 2 situations:

1. Periodically every 1 hour
2. Press the device's test button




This icon will be updated by 3 situations:

1. Periodically every 1 hour
2. Immediately if the CO2 level is more than 1000 ppm
3. Press the device's test button

# Chapter 6 - APP Functions

## MerryIoT Motion Detection(MS10)



## Icons



Battery status  
Sufficient / Low / Exhausted



LoRaWAN Connection status  
On/off



Temperature (oC / oF)



Relative Humidity (%)

Both the icon of Temperature and Relative Humidity will be updated by 2 situations:  
1. Periodically every 1 hour  
2. Press the device's test button



Button pressed  
this icon will be displayed on your app dashboard when you press the device's test button, also the temperature and humidity will be updated at the same time.




Motion detected  
this icon will be displayed on your app dashboard immediately when the device detect a human motion, and the icon will disappear if there is no human detection in the last 5 minutes.




Device is being tampered  
this icon will be displayed on your app dashboard immediately when the device is been moved or tampered

## Chapter 6 - APP Functions

### MerryIoT Open/Close(DW10)






### Icons




Both the icon of Temperature and Relative Humidity will be updated by 2 situations:

1. Periodically every 1 hour
2. Press the device's test button



## Chapter 6 - APP Functions

### MerryIoT Leak Detection(WL10)



### Icons



Battery status  
Sufficient / Low / Exhausted



LoRaWAN Connection status  
On/off



Temperature (oC / oF)



Relative Humidity (%)

Both the icon of Temperature and Relative Humidity will be updated by 2 situations:  
1. Periodically every 1 hour  
2. Press the device's test button



Button pressed

this icon will be displayed on your app dashboard when you press the device's test button, also the temperature and humidity will be updated at the same time.



Water leak detected

this icon will be displayed on your app dashboard immediately when the device detect a leak/flooding event, and the icon will disappear when the water dry up.



Device is being tampered

this icon will be displayed on your app dashboard immediately when the device is been moved or tampered .




## Chapter 7 - Battery Replacement

### MerryIoT Air Quality CO2(CD10)

- 1 Tools: Cross-type screw driver x 1(PH0)




- 2 Remove the battery cover of the sensor with a cross-type screwdriver(PH0 size).



- 3 Replace the battery with new ones(Li-SiO2 battery, "ER14505", AA size x 2 pcs).

\*Caution: Using batteries other than the ones provided may result in loss of performance and battery life, and also damage to the device. Dispose of properly, observing environmental protection rules. Mixing of cells can result in battery leakage and sub-optimal device performance.



X2

ER14505\*


Lithium-thionyl Chloride  
(Li-SOCl<sub>2</sub>) Battery, AA

- 3 Re-assemble the battery cover.


## Chapter 7 - Battery Replacement

### MerryIoT Motion Detection(MS10)

- 1 Tools: Cross-type screw driver x 1(PH0)




- 2 Remove the battery cover of the sensor with a cross-type screwdriver(PH0 size).



- 3 Replace the battery with new ones(Alkaline Battery, "LR6", AA size x 2 pcs).

\*Caution: Using batteries other than the ones provided may result in loss of performance and battery life, and also damage to the device. Dispose of properly, observing environmental protection rules. Mixing of cells can result in battery leakage and sub-optimal device performance.



X2

Alkaline AA

LR6 Alkaline battery, AA

- 3 Re-assemble the battery cover.


## Chapter 7 - Battery Replacement

### MerryIoT Open/Close(DW10)


- 1 Tools: Cross-type screw driver x 1(PH0)



- 2 Remove the battery cover of the sensor with a cross-type screwdriver(PH0 size).



- 3 Replace the battery with new ones(Li-SiO<sub>2</sub> battery, "ER14250", 1/2 AA size x 2 pcs).  
\*Caution: Using batteries other than the ones provided may result in loss of performance and battery life, and also damage to the device. Dispose of properly, observing environmental protection rules. Mixing of cells can result in battery leakage and sub-optimal device performance.



X2

ER14250\*

Lithium-thionyl Chloride  
(Li-SOCl<sub>2</sub>) Battery, 1/2 AA

- 3 Re-assemble the battery cover.


## Chapter 7 - Battery Replacement

### MerryIoT Leak Detection(WL10)


- 1 Tools: Cross-type screw driver x 1(PH1), Star-type screw driver x 1(T8H), Plastic disassembly stick(recommended).



- 2 Remove 4 rubber stands of the sensor with disassembly stick.




- 3 Remove the bottom cover of the sensor with a star-type screwdriver(T8H size).  
\*Caution: Removing the bottom cover may affect the water-tightness. Please get help from Browan team before you do so.



## Chapter 7 - Battery Replacement

### 4 Remove the circuit board of the sensor with a cross-type screw driver x 1(PH1)


\*Caution: Avoid touching the circuit board with bare hand. Touching boards can release static discharge. Please wear a plastic/rubber glove.



### 5 Replace the battery with new ones(Alkaline Battery,"LR6", AA x 2 pcs)

\*Caution: DO NOT remove the battery holder.

\*Caution: Using batteries other than the ones provided may result in loss of performance and battery life, and also damage to the device. Dispose of properly, observing environmental protection rules. Mixing of cells can result in battery leakage and sub-optimal device performance.




### 6 Re-assemble the battery cover.

## Chapter 8 - FAQ

1.

Why do I get the error message "Sorry about that, please report it to us in the app help section" while binding the MerryIoT sensor through the MerryIoT sensor APP?



MerryIoT Air Quality C...

Name  
Test\_CO2

Description  
Bedroom

Location  
Bedroom

Sorry about that, please report it to us in the app help section.

Next

**Answer:**

Since the MerryIoT sensor APP is only for a specific batch number of MerryIoT sensors, kindly check with your supplier whether the one you purchase is for using with the MerryIoT sensor APP.

---

2.

How long will it take to get the CO2 value?

**Answer:**

It takes more than 20 minutes at least to get the CO2 value by manually activation, or 1 hour automatically.

---

3.

Why do I have to "sign in" via Google/Apple ID/Facebook twice?

**Answer:**

The first "sign in" is identified as a presign-up process in AWS Cognito which the MerryIoT Sensor uses to manage third-party social media registration. Once the presign-up is complete, the mobile app page will redirect you to the "sign in" page again, then, you can sign in to the mobile app successfully.

---

For more FAQs please visit <https://www.merryiot.com/FAQ>

## **Chapter 9 - Copyright Notice**

### **Copyright**

© 2021 BROWAN COMMUNICATIONS INC.

This document is copyrighted with all rights reserved. No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language in any form by any means without the written permission of BROWAN COMMUNICATIONS INC.

### **Notice**

BROWAN COMMUNICATIONS INC. reserves the right to change specifications without prior notice.

While this manual has been compiled with great care, it may not be deemed as an assurance of product characteristics. BROWAN COMMUNICATIONS INC. shall be liable only to the degree specified in the terms of sale and delivery.

The reproduction and distribution of the documentation and software supplied with this product and the use of its contents are subject to written authorization from BROWAN COMMUNICATIONS INC.

### **Trademark**

The product described in this document is a licensed product of BROWAN COMMUNICATIONS INC.

## **Contact Us**

Website: <https://www.merryiot.com>

E-mail: [sales@merryiot.com](mailto:sales@merryiot.com)  
[support@merryiot.com](mailto:support@merryiot.com)

Address : Browan Communications Incorporation  
No.15-1 Zhonghua Rd., Hsinchu Industrial Park,  
Hukou, Hsinchu, Taiwan, 30352